



VAPCO PRODUCTS, INC.

**Safety Data Sheet
Coat IT Blue Liquid**

SECTION 1: Identification

GHS Product identifier

Product name	Coat IT Blue Liquid
Product number	CIB-1, CIB-5, CIB-55
Brand	Vapco

Recommended use of the chemical and restrictions on use
Corrosion protection

Supplier's details

Name	Vapco Products, Inc.
Address	401 Marshall Road Valley Park, Missouri 63088 United States

Telephone	(636) 923-2121
Fax	(636) 923-3002
email	info@VapcoProducts.com

Emergency phone number

(800) 255-3924

SECTION 2: Hazard identification

Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200)

- Skin corrosion/irritation, Cat. 1B
- Flammable liquids, Cat. 3

GHS label elements, including precautionary statements

Safety Data Sheet

Pictogram



Signal word

Danger

Hazard statement(s)

H226
H314

Flammable liquid and vapor
Causes severe skin burns and eye damage

Precautionary statement(s)

P210
P233
P240
P243
P260
P264
P280
P301+P330+P331
P303+P361+P353

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash hands and other exposed areas thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER/doctor if exposed or concerned.
Specific treatment (see First Aid on this label).
Wash contaminated clothing before reuse.
In case of fire: Use sand to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container to the specifications of local, regional, national, and international regulations.

P304+P340
P305+P351+P338

P310
P321
P363
P370+P378
P403+P235
P405
P501

SECTION 3: Composition/information on ingredients

Mixtures

Hazardous components

1. Isopropanol

Concentration	1 - 20 % (weight)
EC no.	414-810-0
CAS no.	67-63-0
Index no.	607-403-00-6

2. Butoxyethanol

Concentration	1 - 20 % (weight)
EC no.	203-905-0
CAS no.	111-76-2
Index no.	603-014-00-0

Safety Data Sheet

3. DIMETHYLETHANOLAMINE

Concentration	1 - 10 % (weight)
EC no.	203-542-8
CAS no.	108-01-0
Index no.	603-047-00-0

SECTION 4: First-aid measures

Description of necessary first-aid measures

General advice	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
If inhaled	First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing. Get medical advice/attention.
In case of skin contact	Immediately drench affected area with water for at least 15 minutes. Remove contaminated clothing immediately. Obtain medical attention if irritation develops or persists.
In case of eye contact	Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.
If swallowed	Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

Most important symptoms/effects, acute and delayed

Acute Health Hazards

Symptoms/Injuries: Harmful if inhaled. Causes serious eye and skin irritation. May cause drowsiness and dizziness. Asphyxia by lack of oxygen: risk of death.

Symptoms/Injuries After Eye Contact: Contact causes mild irritation with redness, tearing, and blurred vision.

Indication of immediate medical attention and special treatment needed, if necessary

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: Fire-fighting measures

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Specific hazards arising from the chemical

Explosion Hazard: Container may explode in heat of fire. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

Incompatibility: Reacts with strong oxidizing agents. Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

Special protective actions for fire-fighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use dry chemical, foam, or carbon dioxide (CO₂). Do not breathe fumes from fire or vapors

Safety Data Sheet

from decomposition. Do NOT fight fire when fire reaches containers. Evacuate area. Fight fire remotely due to the risk of explosion. Shut off all sources of ignition. Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. Wear NIOSH-approved Self-Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires.

Hazardous Combustion Products: Carbon oxides (CO, CO₂).

Further information

Do not allow run-off from fire fighting to enter drain or water courses.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapors, spray, mist, gas. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedure: Eliminate ignition source first, then ventilate the area. Evacuate unnecessary personnel, isolate, and ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Environmental precautions

Prevent entry into sewers and public waters. Avoid release to the environment.

Methods and materials for containment and cleaning up

Methods for Containment: Ventilate area. Contain any spills with dikes or absorbents to prevent further migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Eliminate all ignition sources. Ventilate area. Stop the ignition source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Take up liquid spill into absorbent material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

Waste Disposal: Dispose of in accordance with local, regional, national, and international regulations. Containers may be hazardous when empty. Do not flame cut, braze, or weld.

Reference to other sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: Handling and storage

Precautions for safe handling

Additional Hazards When Processed: Do not pressurize, cut, or weld containers. Ruptured cylinders may rocket. Pressurized container: May burst if heated. Do not pierce or burn, even after use.

Precautions for Safe Handling: Do not handle until all safety precautions have been read and understood. Avoid contact with skin, eyes and clothing. Do not breathe gas, mist, spray, vapors. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not spray on open flame or other ignition source.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

Other Precautions: Keep out of reach of children. Follow label instructions. Vapors may collect in low lying area.

Safety Data Sheet

Conditions for safe storage, including any incompatibilities

Technical Measures: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Store in a dry, cool place. Keep only in the original container in a cool, well-ventilated place away from ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

Incompatible Materials: Reacts with strong oxidizing agents.

SECTION 8: Exposure controls/personal protection

Control parameters

CAS: 111-76-2 (EC: 203-905-0)

Butoxyethanol

20 ppm, 97 mg/m³ PEL inhalation; ACGIH (USA): 20 ppm TLV® inhalation; 20 ppm TWA inhalation;
Cal/OSHA: 20 ppm PEL inhalation; NIOSH: 5 ppm REL inhalation; 5 ppm, 24 mg/m³ TWA inhalation; OSHA:
50 ppm PEL inhalation; 240 mg/m³ PEL inhalation; 50 ppm, 240 mg/m³ TWA inhalation

CAS: 67-63-0

Isopropanol

ACGIH (USA): 200 ppm, (ST) 400 ppm TLV® inhalation; Cal/OSHA: 400 ppm, (ST) 500 ppm PEL inhalation;
NIOSH: 400 ppm, (ST) 500 ppm REL inhalation; OSHA: 400 ppm PEL inhalation; 980 mg/m³ PEL inhalation

Appropriate engineering controls

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Use only outdoors or in well-ventilated area. Ensure all local, regional, national, and international regulations are observed. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Individual protection measures, such as personal protective equipment (PPE)

Pictograms



Eye/face protection

Chemical safety goggles. Insufficient ventilation: wear respiratory protection. Respiratory protection of the dependent type.

Skin protection

Wear protective gloves and clothing.

Body protection

Wear suitable protective clothing. Wear protective gloves. Chemical resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

Respiratory protection

Use a NIOSH-approved Self-Containing Breathing Apparatus whenever exposure may exceed established Occupational Exposure Limits.

Safety Data Sheet

SECTION 9: Physical and chemical properties and safety characteristics

Basic physical and chemical properties

Physical state	Liquid
Appearance	Liquid
Color	Blue
Odor	Characteristic
Odor threshold	N/D
Melting point/freezing point	N/D
Boiling point or initial boiling point and boiling range	N/D
Flammability	Not considered a flammable liquid by OSHA (29 CFR 1910.1200)
Lower and upper explosion limit/flammability limit	N/D
Flash point	N/D
Auto-ignition temperature	N/D
Decomposition temperature	N/D
pH	8.0-10.0
Kinematic viscosity	N/D
Solubility	Soluble in water
Partition coefficient n-octanol/water (log value)	N/D
Vapor pressure	N/D
Evaporation rate	N/D
Density and/or relative density	0.95-1.10
Relative vapor density	N/D

Particle characteristics

N/D

Supplemental information regarding physical hazard classes

None

Further safety characteristics (supplemental)

None

SECTION 10: Stability and reactivity

Reactivity

Stable under normal conditions of use.

Chemical stability

Stable under normal conditions of use.

Possibility of hazardous reactions

None known.

Conditions to avoid

Excessive heat will lead to accelerated oxidative degradation.

Incompatible materials

Reacts with strong oxidizing agents.

Hazardous decomposition products

Carbon oxides (CO, CO₂).

Safety Data Sheet

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

The ATE (dermal) of the mixture is: 3666.67 mg/kg bw
The ATE (gas inhalation) of the mixture is: 15000 ppmV
The ATE (vapor inhalation) of the mixture is: 36.67 mg/l
The ATE (oral) of the mixture is: 1666.67 mg/kg bw

2-Butoxyethanol

LD50 Oral - Rat - 880 mg/kg
LD50 Skin - Rabbit - 1,060 mg/kg
LD50 Intraperitoneal - Rat - 220 mg/kg
LD50 Intravenous - Rat - 307 mg/kg
LD50 Oral - Rat - 470 mg/kg
LC50 Inhalation - Rat - 450 ppm
LC50 - *Oncorhynchus mykiss* (rainbow trout) - 1,474 mg/l - 96 h
EC50 - *Daphnia magna* (water flea) - 1,550 mg/l - 48 h
EC50 - *Pseudokirchneriella subcapitata* (green algae) - 1,840 mg/l - 72 h
LC50 - *Daphnia magna* (water flea) - 1,550 mg/l - 48 h
LC50 - *Pseudokirchneriella subcapitata* (green algae) - 911 mg/l - 72 h

ISOPROPANOL

LD50 Oral - Rat - 5,045 mg/kg
LC50 Inhalation - Rat - 16000 ppm - 8 h
LD50 Skin - Rabbit - 12,800 mg/kg
LC50 - *Pimephales promelas* (fathead minnow) - 9,640.00 mg/l - 96 h
EC50 - *Daphnia magna* (water flea) - 5,102.00 mg/l - 24 h
EC50 - *Daphnia magna* (water flea) - 6,851 mg/l - 24 h
EC50 - *Desmodesmus subspicatus* (chodat) - > 2,000.00 mg/l - 72 h
EC50 - Algae - > 1,000.00 mg/l - 24 h

Skin corrosion/irritation

Causes mild skin irritation.

Serious eye damage/irritation

Causes serious eye irritation, redness, burning.

Respiratory or skin sensitization

Acute oral and inhalation toxicity category 5.

Germ cell mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

STOT-single exposure

May cause drowsiness or dizziness.

Safety Data Sheet

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Harmful if inhaled. Causes serious eye irritation. May cause drowsiness and dizziness. Asphyxia by lack of oxygen: risk of death.

SECTION 12: Ecological information

Toxicity

2-Butoxyethanol

LD50 Oral - Rat - 880 mg/kg

LD50 Skin - Rabbit - 1,060 mg/kg

LD50 Intraperitoneal - Rat - 220 mg/kg

LD50 Intravenous - Rat - 307 mg/kg

LD50 Oral - Rat - 470 mg/kg

LC50 Inhalation - Rat - 450 ppm

LC50 - *Oncorhynchus mykiss* (rainbow trout) - 1,474 mg/l - 96 h

EC50 - *Daphnia magna* (water flea) - 1,550 mg/l - 48 h

EC50 - *Pseudokirchneriella subcapitata* (green algae) - 1,840 mg/l - 72 h

LC50 - *Daphnia magna* (water flea) - 1,550 mg/l - 48 h

LC50 - *Pseudokirchneriella subcapitata* (green algae) - 911 mg/l - 72 h

ISOPROPANOL

LD50 Oral - Rat - 5,045 mg/kg

LC50 Inhalation - Rat - 16000 ppm - 8 h

LD50 Skin - Rabbit - 12,800 mg/kg

LC50 - *Pimephales promelas* (fathead minnow) - 9,640.00 mg/l - 96 h

EC50 - *Daphnia magna* (water flea) - 5,102.00 mg/l - 24 h

EC50 - *Daphnia magna* (water flea) - 6,851 mg/l - 24 h

EC50 - *Desmodesmus subspicatus* (chodat) - > 2,000.00 mg/l - 72 h

EC50 - Algae - > 1,000.00 mg/l - 24 h

Persistence and degradability

Not classified.

Bioaccumulative potential

Not classified.

Mobility in soil

Not classified.

Other adverse effects

Avoid release to the environment. This material is hazardous to aquatic life. Do not let residue come in contact with waterways.

SECTION 13: Disposal considerations

Disposal methods

Product disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations. Do not pierce or burn, even after use.

Safety Data Sheet

Sewage disposal

Avoid release into the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

Other disposal recommendations

Container may remain hazardous when empty. Continue to observe all precautions. Do not puncture or incinerate container.

SECTION 14: Transport information

DOT (US)

UN Number: UN2920

Class: 8 (3)

Packing Group: II

Proper Shipping Name: Corrosive liquids, flammable, n.o.s.

IMDG

UN Number: UN2920

Class: 8 (3)

Packing Group: II

EMS Number: N/A

Proper Shipping Name: Corrosive liquids, flammable, n.o.s.

IATA

UN Number: UN2920

Class: 8 (3)

Packing Group: II

Proper Shipping Name: Corrosive liquids, flammable, n.o.s.

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Massachusetts Right To Know Components

Isopropyl alcohol

CAS number: 67-63-0

Ethylene glycol monobutyl ether

CAS: 111-76-2

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard, Acute Health Hazard

Safety Data Sheet

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Isopropyl alcohol

CAS number: 67-63-0

The following components are subject to reporting levels established by SARA Title III, Section 313:

Ethylene glycol monobutyl ether

CAS: 111-76-2

Toxic Substances Control Act (TSCA) Inventory

All chemicals are listed or exempt.

SECTION 16: Other information

N/A = Not applicable; N/D = Not determined

Further information/disclaimer

To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.

Preparation information

Preparation by: Jessica Wilson

Date prepared: 10/25/2022