



VAPCO PRODUCTS, INC.

Safety Data Sheet Foaminator Cylinder

SECTION 1: Identification

1.1 GHS Product identifier

Product name	Foaminator Cylinder
Product number	FM-SC, FM-LC
Brand	Vapco

1.3 Recommended use of the chemical and restrictions on use

Non-acid, alkaline-based coil cleaner

1.4 Supplier's details

Name	Vapco Products, Inc.
Address	401 Marshall Road Valley Park, Missouri 63088 United States
Telephone	(636) 923-2121
Fax	(636) 923-3002
email	info@VapcoProducts.com

1.5 Emergency phone number

(800) 255-3924

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200, 2012)

- Eye damage/irritation, Cat. 1
- Corrosive to metals, Cat. 1
- Gases under pressure, compressed gas
- Skin corrosion/irritation, Cat. 1A

2.2 GHS label elements, including precautionary statements

Safety Data Sheet

Pictograms



Signal word

Danger

Hazard statement(s)

H280

Contains gas under pressure; may explode if heated

H290

May be corrosive to metals

H314

Causes severe skin burns and eye damage

Precautionary statement(s)

P234

Keep only in original container.

P260

Do not breathe dust/fume/gas/mist/vapors/spray.

P264

Wash hands thoroughly after handling.

P280

Wear eye protection/face protection.

P301+P330+P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTER/doctor.

P321

Specific treatment (see First Aid on this label).

P363

Wash contaminated clothing before reuse.

P390

Absorb spillage to prevent material-damage.

P406

Store in a corrosive resistant container with a resistant inner liner.

P410+P403

Protect from sunlight. Store in a well-ventilated place.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

1. N-Butane

Concentration

1 - 2 % (weight)

EC no.

203-448-7

CAS no.

106-97-8

Index no.

601-004-01-8

2. Propane, liquid

Concentration

1 - 10 % (weight)

EC no.

200-827-9

CAS no.

74-98-6

Index no.

601-003-00-5

Safety Data Sheet

3. Sodium Hydroxide

Concentration	1 - 10 % (weight)
EC no.	215-185-5
CAS no.	1310-73-2
Index no.	011-002-00-6

4. Ammonium hydroxide ((NH₄)(OH))

Concentration	0.1 - 1 % (weight)
EC no.	215-647-6
CAS no.	1336-21-6
Index no.	007-001-01-2

5. D-Glucopyranose, oligomeric, decyl octyl glycosides

Concentration	0.1 - 1 % (weight)
CAS no.	68515-73-1

6. C10_16-alkyl, oligomeric, D-glucopyranoside

Concentration	0.1 - 1 % (weight)
CAS no.	110615-47-9

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General advice	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
If inhaled	First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing. Get medical advice/attention.
In case of skin contact	Immediately drench affected area with water for at least 15 minutes. Remove contaminated clothing immediately. Obtain medical attention if irritation develops or persists.
In case of eye contact	Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.
If swallowed	Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2 Most important symptoms/effects, acute and delayed

Symptoms/Injuries: Harmful if inhaled. May cause severe burns on skin and eyes. May cause drowsiness and dizziness. Asphyxia by lack of oxygen: risk of death.

4.3 Indication of immediate medical attention and special treatment needed, if necessary

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand. Note to Physician: The absence of visible signs or symptoms of burns does not reliably exclude the presence of actual tissue damage.

Safety Data Sheet

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, dry chemical, or sand. Use appropriate media for surrounding fire.

5.2 Specific hazards arising from the chemical

Explosion Hazard: Container may explode in heat of fire. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

Incompatibility: Organic materials, concentrated acids, metals. May react with certain food sugars.

5.3 Special protective actions for fire-fighters

Precautionary Fire Measures: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use dry chemical, foam, or carbon dioxide (CO₂). Do not breathe fumes from fire or vapors from decomposition. Do NOT fight fire when fire reaches containers. Evacuate area. Fight fire remotely due to the risk of explosion. Shut off all sources of ignition. Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. Wear NIOSH-approved Self-Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires.

Hazardous Combustion Products: Carbon oxide(s) and nitrogen oxide(s).

Further information

Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapors, spray, mist, gas. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedure: Eliminate ignition sources first, then ventilate the area. Evacuate unnecessary personnel, isolate, and ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2 Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3 Methods and materials for containment and cleaning up

For Containment: Ventilate the area. Contain any spills with dikes or absorbents to prevent further migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Eliminate all ignition sources. Ventilate area. Stop the ignition source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Take up liquid spill into absorbent material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

Safety Data Sheet

Waste Disposal: Dispose of in accordance with local, regional, national, and international regulations. Containers may be hazardous when empty. Do not flame cut, braze, or weld. Product should be fully characterized prior to disposal (40 CFR 261).

Reference to other sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Additional Hazards When Processed: Do not pressurize, cut, or weld containers. Ruptured cylinders may rocket. Pressurized container: May burst if heated. Do not pierce or burn, even after use.

Precautions for Safe Handling: Do not handle until all safety precautions have been read and understood. Avoid contact with skin, eyes and clothing. Do not breathe gas, mist, spray, vapors. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not spray on open flame or other ignition source.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

Other Precautions: Keep out of reach of children. Follow label instructions. Vapors may collect in low lying areas.

7.2 Conditions for safe storage, including any incompatibilities

Technical Measures: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Store in a dry, cool place. Keep only in the original container in a cool, well-ventilated place away from ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

Incompatible Materials: Organic materials, concentrated nitric acids, metals. May react with certain food sugars.

Storage Temperature: <50°C/122°F.

Specific end use(s)

Alkaline-based coil cleaner

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. N-Butane (CAS: 106-97-8)

TWA [Butane] (Inhalation): 800 ppm; 1900 mg/m³; AU (AU/SWA)

2. Propane, liquid (CAS: 74-98-6)

PEL [Propane] (Inhalation): 1000 ppm; US (US/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL [Propane] (Inhalation): 1800 mg/m³; US (US/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL [Propane] (Inhalation): 1000 ppm; US (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL [Propane] (Inhalation): 1000 ppm; US (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

3. Sodium hydroxide (CAS: 1310-73-2)

TWA (Inhalation): 2 Peak limitation mg/m³; AU (AU/SWA)

Safety Data Sheet

PEL (Inhalation): 2 mg/m³; US (US/OSHA)
OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): (C) 2 mg/m³; US (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): (C) 2 mg/m³; US (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov

8.2 Appropriate engineering controls

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Use only outdoors or in well-ventilated area. Ensure all local, regional, national, and international regulations are being observed. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Chemical safety goggles. Insufficient ventilation: wear respiratory protection. Respiratory protection of the dependent type.

Skin protection

Wear protective gloves and clothing.

Body protection

Wear suitable protective clothing. Wear protective gloves. Chemical resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.

Respiratory protection

Use a NIOSH-approved Self-Containing Breathing Apparatus whenever exposure may exceed established Occupational Exposure Limits.

SECTION 9: Physical and chemical properties

Basic physical and chemical properties

Physical state	Liquid
Appearance	Pressurized spray
Color	Yellow
Odor	Bland odor
Odor threshold	N/D
Melting point/freezing point	N/D
Boiling point or initial boiling point and boiling range	N/D
Flammability	Not considered a flammable aerosol or an extremely flammable aerosol by OSHA (29 CFR 1910.1200)
Lower and upper explosion limit/flammability limit	N/D
Flash point	N/D
Explosive properties	Pressurized cylinder; may burst if heated
Auto-ignition temperature	N/D
Decomposition temperature	N/D
pH	11-14
Kinematic viscosity	N/D

Safety Data Sheet

Solubility	Completely soluble in water
Partition coefficient n-octanol/water (log value)	N/D
Vapor pressure	1 at 77°F (25°C)
Evaporation rate	<0.8 Slow
Density and/or relative density	1.12 at 77°F (25°C)
Relative vapor density	N/D

SECTION 10: Stability and reactivity

10.1 Reactivity

Chemically active metals and acids.

10.2 Chemical stability

Contains gas under pressure; may explode if heated. Pressurized container; may burst if heated.

10.3 Possibility of hazardous reactions

None known.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Organic materials, concentrated acids, metals. May react with certain food sugars.

10.6 Hazardous decomposition products

Carbon oxide(s), nitrogen oxide(s).

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Alkyl polyglycoside

LC50 Inhalation - >20 mg/l (vapor) ATE; >5 mg/l (mist) ATE

LD50 Skin - Rabbit - >5,000 mg/kg

LD50 Oral - Rat - >5,000 mg/kg

Skin corrosion/irritation

Causes severe burns, prolonged contact will destroy tissue.

Serious eye damage/irritation

Causes severe burns, irritation, redness, tearing, pain, may result in loss of sight.

Respiratory or skin sensitization

May cause irritation (possible severe), chemical burns, upper respiratory damage, and pulmonary edema.

Germ cell mutagenicity

Not classified.

Carcinogenicity

Not classified.

Safety Data Sheet

Reproductive toxicity

Not classified.

Specific target organ toxicity (STOT) - single exposure

May cause severe burns. May cause drowsiness or dizziness.

Specific target organ toxicity (STOT) - repeated exposure

Dermatitis may occur due to long-term irritation.

Aspiration hazard

Harmful if inhaled. Causes serious eye irritation. May cause drowsiness and dizziness. Asphyxia by lack of oxygen: risk of death.

SECTION 12: Ecological information

Toxicity

Alkyl polyglucoside

EC50 - *Desmodesmus subspicatus* (chodat) - 10-100 mg/l - 72 hrs

EC50 - *Daphnia magna* (water flea) - 10-100 mg/l - 48 hrs

LC50 - Fish - 10-100 mg/l - 96 hrs

D-glucopyranose, oligomeric, decyl octyl glycosides

LC50 - Fish - 170 mg/l - 96 hrs

Sodium hydroxide

LC50 - *Gambusia affinis* (mosquito fish) - 125 mg/l - 96 hrs

LC50 - *Oncorhynchus mykiss* (rainbow trout) - 45.4 mg/l - 96 hrs

EC50 - *Daphnia magna* (water flea) - 40.38 mg/l - 48 hrs

LC50 - *Poecilia reticulata* (guppy) - 196 mg/l - 96 hrs

Persistence and degradability

This product is biodegradable.

Bioaccumulative potential

This product is not expected to bioaccumulate.

Mobility in soil

This product is mobile in soil.

Other adverse effects

Avoid release to the environment. Do not let residue come in contact with waterways.

SECTION 13: Disposal considerations

Disposal methods

Product disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations. Do not pierce or burn, even after use.

Safety Data Sheet

Waste treatment

Check the pH of the waste to be disposed - if it is greater than 12.5, it must be handled as a RCRA hazardous waste. May be subject to disposal regulations U.S. EPA 40 CFR 261. Hazardous waste number(s): D002.

Sewage disposal

Avoid release into the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

Other disposal recommendations

Container may remain hazardous when empty. Continue to observe all precautions. Do not puncture or incinerate container. Product should be fully characterized prior to disposal.

SECTION 14: Transport information

DOT (US)

UN Number: UN1956

Class: 2.2

Packing Group: N/A

Proper Shipping Name: Compressed gas, n.o.s

IMDG

UN Number: UN1956

Class: 2.2

Packing Group: N/A

EMS Number: N/A

Proper Shipping Name: Compressed gas, n.o.s

IATA

UN Number: UN1956

Class: 2.2

Packing Group: N/A

Proper Shipping Name: Compressed gas, n.o.s

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Massachusetts Right To Know Components (105 CMR 670)

Chemical name: BUTANE

CAS number: 106-97-8

Chemical name: PROPANE

CAS number: 74-98-6

Chemical name: SODIUM HYDROXIDE

CAS number: 1310-73-2

Chemical name: AMMONIUM HYDROXIDE

CAS number: 1336-21-6

Safety Data Sheet

Massachusetts Toxic Use Reduction Act (TURA) list

Chemical name: Sodium hydroxide

CAS number: 1310-73-2

Chemical name: Ammonium hydroxide

CAS number: 1336-21-6

New Jersey Right To Know Components

Common name: BUTANE

CAS number: 106-97-8

Common name: PROPANE

CAS number: 74-98-6

Common name: SODIUM HYDROXIDE

CAS number: 1310-73-2

Common name: AMMONIUM HYDROXIDE

CAS number: 1336-21-6

Pennsylvania Right To Know Components

Chemical name: BUTANE

CAS number: 106-97-8

Chemical name: PROPANE

CAS number: 74-98-6

Chemical name: SODIUM HYDROXIDE (NA(OH))

CAS number: 1310-73-2

Chemical name: AMMONIUM HYDROXIDE ((NH4)(OH))

CAS number: 1336-21-6

US EPA TSCA public inventory

Chemical name: N-Butane

CAS number: 106-97-8

Chemical name: Propane, liquid

CAS number: 74-98-6

Chemical name: Sodium Hydroxide

CAS number: 1310-73-2

Chemical name: Ammonium hydroxide ((NH4)(OH))

CAS number: 1336-21-6

Chemical name: D-Glucopyranose, oligomeric, decyl octyl glycosides

CAS number: 68515-73-1

Chemical name: C10_16-alkyl, oligomeric, D-glucopyranoside

CAS number: 110615-47-9

SECTION 16: Other information

N/A = Not applicable; N/D = Not determined

16.1 Further information/disclaimer

To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.

16.2 Preparation information

Prepared by: Jessica Wilson

Date prepared: 2/17/2025

