



VAPCO PRODUCTS, INC.

Safety Data Sheet Stick It Kwik

SECTION 1: Identification

1.1 GHS Product identifier

Product name	Stick It Kwik
Product number	STK-LC, STK-SC
Brand	Vapco

1.3 Recommended use of the chemical and restrictions on use

Water-based adhesive cylinder

1.4 Supplier's details

Name	Vapco Products, Inc.
Address	401 Marshall Road Valley Park, Missouri 63088 USA

Telephone	(636) 923-2121
Fax	(636) 923-3002
email	info@VapcoProducts.com

1.5 Emergency phone number

(800) 255-3924

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200, 2024)

- Eye damage/irritation, Cat. 2A
- Gases under pressure, compressed gas
- Skin corrosion/irritation, Cat. 2

2.2 GHS label elements, including precautionary statements

Safety Data Sheet

Pictograms



Signal word

Warning

Hazard statement(s)

H280

Contains gas under pressure; may explode if heated

H315

Causes skin irritation

H319

Causes serious eye irritation

Precautionary statement(s)

P264

Wash hands thoroughly after handling.

P280

Wear eye protection/face protection/protective gloves.

P302+P352

IF ON SKIN: Wash with plenty of water.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P321

Specific treatment (see First Aid on this label).

P332+P313

If skin irritation occurs: Get medical advice/attention.

P337+P313

If eye irritation persists: Get medical advice/attention.

P362+P364

Take off contaminated clothing and wash it before reuse.

P410+P403

Protect from sunlight. Store in a well-ventilated place.

P412

Do not expose to temperatures exceeding 50 °C/122 °F.

P501

Dispose of contents/container to the specifications of local, regional, national, and international regulations.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

1. Styrene-acrylic copolymer

Concentration

45 - 55 % (weight)

CAS no.

25085-19-2

2. Petroleum gases, liquified, sweetened, if they contain > 0.1% w/w Butadiene

Concentration

10 - 20 % (weight)

CAS no.

68476-86-8

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General advice

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

If inhaled

First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing. Get medical advice/attention.

Safety Data Sheet

In case of skin contact	Immediately drench affected area with water for at least 15 minutes. Remove contaminated clothing immediately. Obtain medical attention if irritation develops or persists.
In case of eye contact	Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.
If swallowed	Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2 Most important symptoms/effects, acute and delayed

None known.

4.3 Indication of immediate medical attention and special treatment needed, if necessary

None known.

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, dry chemical, or sand. Use appropriate media for surrounding fire.

5.2 Specific hazards arising from the chemical

Explosion Hazard: Container may explode in heat of fire. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

Incompatibilities: None known.

5.3 Special protective actions for fire-fighters

Precautionary Fire Measures: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use dry chemical, foam, or carbon dioxide (CO₂). Do not breathe fumes from fire or vapors from decomposition. Do NOT fight fire when fire reaches containers. Evacuate area. Fight fire remotely due to the risk of explosion. Shut off all sources of ignition. Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. Wear NIOSH-approved Self-Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires.

Hazardous Combustion Products: Carbon oxide(s) and various hydrocarbons.

Further information

Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapors, spray, mist, gas. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedure: Eliminate ignition sources first, then ventilate the area. Evacuate unnecessary personnel, isolate, and ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of

Safety Data Sheet

dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

5.2 Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

5.3 Methods and materials for containment and cleaning up

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Eliminate all ignition sources. Ventilate area. Stop the ignition source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Take up liquid spill into absorbent material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

For Containment: Ventilate the area. Contain any spills with dikes or absorbents to prevent further migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Waste Disposal: Dispose of in accordance with local, regional, national, and international regulations. Containers may be hazardous when empty. Do not flame cut, braze, or weld. Product should be fully characterized prior to disposal (40 CFR 261).

Reference to other sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Precautions for Safe Handling: Do not handle until all safety precautions have been read and understood. Avoid contact with skin, eyes and clothing. Do not breathe gas, mist, spray, vapors. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not spray on open flame or other ignition source.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

Other Precautions: Keep out of reach of children. Follow label instructions. Vapors may collect in low lying areas.

Additional Hazards When Processed: Do not pressurize, cut, or weld containers. Ruptured cylinders may rocket. Pressurized container: May burst if heated. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

Technical Measures: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Store in a dry, cool place. Keep only in the original container in a cool, well-ventilated place away from ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

Incompatible Materials: None known.

Specific end use(s)

Water-based adhesive spray cylinder

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. Petroleum gases, liquified, sweetened, if they contain > 0.1% w/w Butadiene (CAS: 68476-86-8)

TWA (Inhalation): 1000 ppm; USA (ACGIH)

REL-TWA (Inhalation): 1800 mg/m³; 800 ppm; USA (NIOSH)

IDLH (Inhalation): 2100 ppm (10% LEL); USA (IDLH)

Safety Data Sheet

PEL-TWA (Inhalation): 1800 mg/m³; 1000 ppm; USA (US/OSHA)

STEL (Inhalation): 1000 ppm; USA (ACGIH)

8.2 Appropriate engineering controls

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Use only outdoors or in well-ventilated area. Ensure all local, regional, national, and international regulations are being observed. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Chemical safety goggles. Insufficient ventilation: wear respiratory protection. Respiratory protection of the dependent type.

Skin protection

Wear protective gloves and clothing.

Body protection

Wear suitable protective clothing. Wear protective gloves. Chemical resistant materials and fabrics. Wear fire/flamm resistant/retardant clothing.

Respiratory protection

Use a NIOSH-approved Self-Containing Breathing Apparatus whenever exposure may exceed established Occupational Exposure Limits.

SECTION 9: Physical and chemical properties

Basic physical and chemical properties

Physical state	Liquid
Appearance	Aerosol spray
Color	White
Odor	Fruity
Odor threshold	N/A
Melting point/freezing point	32 °F
Boiling point or initial boiling point and boiling range	212 °F
Flammability	Not considered a flammable aerosol by OSHA (29 CFR 1910.1200)
Lower and upper explosion limit/flammability limit	N/D
Flash point	N/A
Auto-ignition temperature	N/D
Decomposition temperature	N/D
pH	3.5-4.5 estimated
Kinematic viscosity	20 - 1,100 cPs
Solubility	Dispersible in water
Partition coefficient n-octanol/water (log value)	N/A
Vapor pressure	N/D
Evaporation rate	N/D
Density and/or relative density	7.9 - 8.9 lb/gal
Relative vapor density	N/D
Particle characteristics	Solids Content, % by weight: 54 - 58

Safety Data Sheet

Supplemental information regarding physical hazard classes

N/A

Further safety characteristics (supplemental)

N/A

SECTION 10: Stability and reactivity

10.1 Reactivity

None known.

10.2 Chemical stability

Material is stable under normal conditions of use.

10.3 Possibility of hazardous reactions

None known.

10.4 Conditions to avoid

Excessive heat.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Carbon oxide(s) and various hydrocarbons.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Petroleum gases, liquified, sweetened, if they contain > 0.1% w/w Butadiene
LC50 Inhalation - Rat - 658 mg/l - 4 h

Skin corrosion/irritation

Product can cause skin irritation.

Serious eye damage/irritation

Product can cause serious eye irritation.

Respiratory or skin sensitization

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

Safety Data Sheet

Specific target organ toxicity (STOT) - single exposure

No data available.

Specific target organ toxicity (STOT) - repeated exposure

No data available.

Aspiration hazard

No data available.

SECTION 12: Ecological information

Toxicity

Petroleum gases, liquified, sweetened, if they contain > 0.1% w/w Butadiene
LC50 Inhalation - Rat - 658 mg/l - 4 h

Persistence and degradability

No data available.

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

SECTION 13: Disposal considerations

Disposal methods

Product disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations. Do not pierce or burn, even after use.

Waste treatment

This material, as supplied, is hazardous waste according to federal regulations (U.S. EPA 40CFR 261). Dispose of in accordance with federal, state, and local regulations.

Other disposal recommendations

Container may remain hazardous when empty. Continue to observe all precautions. Do not puncture or incinerate container. Product should be fully characterized prior to disposal.

SECTION 14: Transport information

DOT (US)

UN Number: UN1956

Class: 2.2

Packing Group: N/A

Proper Shipping Name: Compressed gas, n.o.s.

IMDG

UN Number: UN1956

Class: 2.2

Packing Group: N/A

EMS Number: N/A

Proper Shipping Name: Compressed gas, n.o.s.

Safety Data Sheet

IATA

UN Number: UN1956

Class: 2.2

Packing Group: N/A

Proper Shipping Name: Compressed gas, n.o.s.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Massachusetts Right To Know Components

Chemical name: Petroleum gases, liquified, sweetened, if they contain > 0.1% w/w Butadiene

CAS number: 68476-86-8

New Jersey Right To Know Components

Chemical name: Petroleum gases, liquified, sweetened, if they contain > 0.1% w/w Butadiene

CAS number: 68476-86-8

Pennsylvania Right To Know Components

Chemical name: Petroleum gases, liquified, sweetened, if they contain > 0.1% w/w Butadiene

CAS number: 68476-86-8

SARA 311/312 Hazards

Acute Health Hazard, Fire Hazard, Sudden Release of Pressure Hazard

Toxic Substances Control Act (TSCA) Inventory

All chemicals are listed or exempt.

SECTION 16: Other information

N/A = Not applicable; N/D = Not determined

16.1 Further information/disclaimer

To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.

16.2 Preparation information

Prepared by: Jessica Wilson

Date prepared: 6/9/2025