



VAPCO PRODUCTS, INC.

Safety Data Sheet Coat IT Cleanup

SECTION 1: Identification

1.1 GHS Product identifier

Product name	Coat IT Cleanup
Product number	CIR-16OZ
Brand	Vapco

1.3 Recommended use of the chemical and restrictions on use

Coating remover

1.4 Supplier's details

Name	Vapco Products, Inc.
Address	401 Marshall Road Valley Park, Missouri 63088 United States
Telephone	(636) 923-2121
Fax	(636) 923-3002
email	info@VapcoProducts.com

1.5 Emergency phone number

(800) 255-3924

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200, 2012)

- Acute toxicity, inhalation, Cat. 4
- Eye damage/irritation, Cat. 2A
- Flammable liquids, Cat. 2
- Specific target organ toxicity (single exposure), Cat. 3

2.2 GHS label elements, including precautionary statements

Safety Data Sheet

Pictograms



Signal word

Warning

Hazard statement(s)

H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness

Precautionary statement(s)

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use appropriate media to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to the specifications of local, regional, national, and international regulations.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

1. Trans-1,2-dichloroethylene

Concentration	60 - 80 % (weight)
EC no.	205-860-2
CAS no.	156-60-5
Index no.	602-026-00-3

Safety Data Sheet

2. Ethanol

Concentration	10 - 30 % (weight)
EC no.	200-578-6
CAS no.	64-17-5
Index no.	603-002-00-5

3. Acetone

Concentration	5 - 15 % (weight)
EC no.	200-662-2
CAS no.	67-64-1
Index no.	606-001-00-8

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General advice	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
If inhaled	First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing. Get medical advice/attention.
In case of skin contact	Immediately drench affected area with water for at least 15 minutes. Remove contaminated clothing immediately. Obtain medical attention if irritation develops or persists.
In case of eye contact	Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.
If swallowed	Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2 Most important symptoms/effects, acute and delayed

Symptoms/Injuries: Harmful if inhaled. Causes serious eye irritation. May cause drowsiness and dizziness. Asphyxia by lack of oxygen: risk of death. May cause frostbite on contact with the liquid.

Symptoms/Injuries After Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms. Inhalation is likely to cause adverse health effects including, but not limited to: irritation, difficulty breathing, and unconsciousness. In elevated concentrations, may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death. This product contains chlorinated solvent material, which is associated with cardiac sensitization following very high exposures or with concurrent exposure to high stress levels or heart-stimulating substances like epinephrine and catecholamines. Careful consideration should be applied preceding administration of epinephrine or similar heart-stimulating substances.

Symptoms/Injuries After Skin Contact: Contact with liquid escaping the container can cause frostbite and freeze burns.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva. Contact with liquid escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Safety Data Sheet

Symptoms/Injuries After Ingestion: Not considered a potential route of exposure, but contact with liquid escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None known.

4.3 Indication of immediate medical attention and special treatment needed, if necessary

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, dry chemical, or sand. Use appropriate media for surrounding fire.

5.2 Specific hazards arising from the chemical

Explosion Hazard: Container may explode in heat of fire. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion. Certain mixtures of chlorinated solvent may be flammable or reactive under certain conditions.

5.3 Special protective actions for fire-fighters

Precautionary Fire Measures: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use dry chemical, foam, or carbon dioxide (CO₂). Do not breathe fumes from fire or vapors from decomposition. Do NOT fight fire when fire reaches containers. Evacuate area. Fight fire remotely due to the risk of explosion. Shut off all sources of ignition. Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. Wear NIOSH-approved Self-Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires.

Hazardous Combustion Products: Carbon oxide(s), chlorine compounds, hydrogen chloride.

Further information

Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapors, spray, mist, gas. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedure: Eliminate ignition sources first, then ventilate the area. Evacuate unnecessary personnel, isolate, and ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2 Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Safety Data Sheet

6.3 Methods and materials for containment and cleaning up

For Containment: Ventilate the area. Contain any spills with dikes or absorbents to prevent further migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Eliminate all ignition sources. Ventilate area. Stop the ignition source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Take up liquid spill into absorbent material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

Waste Disposal: Dispose of in accordance with local, regional, national, and international regulations. Containers may be hazardous when empty. Do not flame cut, braze, or weld. Product should be fully characterized prior to disposal (40 CFR 261).

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Additional Hazards When Processed: Do not pressurize, cut, or weld containers. Ruptured cylinders may rocket. Pressurized container: May burst if heated. Do not pierce or burn, even after use.

Precautions for Safe Handling: Do not handle until all safety precautions have been read and understood. Avoid contact with skin, eyes and clothing. Do not breathe gas, mist, spray, vapors. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not spray on open flame or other ignition source.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

Other Precautions: Keep out of reach of children. Follow label instructions. Vapors may collect in low lying areas.

7.2 Conditions for safe storage, including any incompatibilities

Technical Measures: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Store in a dry, cool place. Keep only in the original container in a cool, well-ventilated place away from ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Chlorine. Finely divided metals. Magnesium. Alkaline earth metals.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. Ethanol (CAS: 64-17-5)

TWA [Ethyl alcohol] (Inhalation): 1000 ppm; 1880 mg/m³; AU (AU/SWA)

PEL [Ethyl alcohol (Ethanol)] (Inhalation): 1000 ppm; US (US/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL [Ethyl alcohol (Ethanol)] (Inhalation): 1900 mg/m³; US (US/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL [Ethyl alcohol (Ethanol)] (Inhalation): 1000 ppm; US (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL [Ethyl alcohol (Ethanol)] (Inhalation): 1000 ppm; US (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

Safety Data Sheet

2. Acetone (CAS: 67-64-1)

TWA (Inhalation): 500 ppm; 1185 mg/m³; AU (AU/SWA)

STEL (Inhalation): 1000 ppm; 2375 mg/m³; AU (AU/SWA)

IOELV-LTEL (Inhalation): 1210 mg/m³; EU (EU/OSHA)

List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

IOELV-LTEL (Inhalation): 500 ppm; EU (EU/OSHA)

List no. 1 under Council Directive 98/24/EC as amended. List last updated on 8/29/2023.

PEL (Inhalation): 1000 ppm; US (US/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 2400 mg/m³; US (US/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 500 ppm, (ST) 750 ppm, (C) 3000 ppm; US (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 250 ppm; US (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

8.2 Appropriate engineering controls

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Use only outdoors or in well-ventilated area. Ensure all local, regional, national, and international regulations are being observed. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Chemical safety goggles. Insufficient ventilation: wear respiratory protection. Respiratory protection of the dependent type.

Skin protection

Wear protective gloves and clothing.

Body protection

Wear suitable protective clothing. Wear protective gloves. Chemical resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

Respiratory protection

Use a NIOSH-approved Self-Containing Breathing Apparatus whenever exposure may exceed established Occupational Exposure Limits.

SECTION 9: Physical and chemical properties

Basic physical and chemical properties

Physical state

Appearance

Color

Odor

Odor threshold

Liquid

Clear liquid

Colorless

Sweet chlorinated solvent

N/D

Safety Data Sheet

Melting point/freezing point	N/D
Boiling point or initial boiling point and boiling range	N/D
Flammability	Considered to be a flammable liquid by OSHA (29 CFR 1910.1200)
Lower and upper explosion limit/flammability limit	N/D
Flash point	N/D
Auto-ignition temperature	N/D
Decomposition temperature	N/D
pH	N/A
Kinematic viscosity	N/D
Solubility	N/D
Partition coefficient n-octanol/water (log value)	N/D
Vapor pressure	N/D
Evaporation rate	Fast
Density and/or relative density	N/D
Relative vapor density	N/D

SECTION 10: Stability and reactivity

10.1 Reactivity

Reacts violently with strong oxidizers. Increased risk of fire or explosion. Certain mixtures of chlorine may be flammable or reactive under certain conditions.

10.2 Chemical stability

Certain mixtures of chlorine may be flammable or reactive under certain conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4 Conditions to avoid

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

10.5 Incompatible materials

Strong acids, strong bases, strong oxidizers. Chlorine. Finely divided metals. Magnesium. Alkaline earth metals.

10.6 Hazardous decomposition products

Thermal decomposition may produce: Carbon oxide(s), chlorine compounds, hydrogen chloride.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Acetone

LD50 Skin - Guinea pig - 7429 mg/kg

LC50 Inhalation - Rat - 50100 mg/m3 - 8 hrs

LD50 Oral - Rat - 5800 mg/kg

Ethanol

LD50 Oral - Rat - 10470 mg/kg

LD50 Skin - Rabbit - 15800 mg/kg

Safety Data Sheet

LD50 Inhalation - Rat - 30000 mg/l - 4 hrs

Skin corrosion/irritation

Causes irritation, redness, burning.

Serious eye damage/irritation

Causes irritation, redness, tearing.

Respiratory or skin sensitization

Causes dizziness, headaches, nausea, central nervous system depression, excessive or prolonged exposure may cause unconsciousness.

Germ cell mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

Specific target organ toxicity (STOT) - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity (STOT) - repeated exposure

Not classified.

Aspiration hazard

The ATE (gas inhalation) of the mixture is: 5625 ppmV.

Additional information

Symptoms/Injuries: Harmful if inhaled. Causes serious eye irritation. May cause drowsiness and dizziness. Asphyxia by lack of oxygen: risk of death. May cause frostbite on contact with the liquid.

Symptoms/Injuries After Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms. Inhalation is likely to cause adverse health effects including, but not limited to: irritation, difficulty breathing, and unconsciousness. In elevated concentrations, may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death. This product contains chlorinated solvent material, which is associated with cardiac sensitization following very high exposures or with concurrent exposure to high stress levels or heart-stimulating substances like epinephrine and catecholamines. Careful consideration should be applied preceding administration of epinephrine or similar heart-stimulating substances.

Symptoms/Injuries After Skin Contact: Contact with liquid escaping the container can cause frostbite and freeze burns.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva. Contact with liquid escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Symptoms/Injuries After Ingestion: Not considered a potential route of exposure, but contact with liquid escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None known.

Safety Data Sheet

SECTION 12: Ecological information

Toxicity

Acetone

LC50 - Oncorhynchus mykiss (rainbow trout) - 5540 mg/l - 96 hrs

LC50 - Daphnia magna (water flea) - 8800 mg/l - 48 hrs

Ethanol

EC50 - Chlorella vulgaris (fresh water algae) - 275 mg/l - 72 hrs

LC50 - Pimephales promelas (fathead minnow) - 14200 mg/l - 96 hrs

LC50 - Ceriodaphnia dubia (water flea) - 5012 mg/l - 48 hrs

Trans-1,2-dichloroethylene

EC50 - Daphnia magna (water flea) - 220 mg/l

Persistence and degradability

Component(s) of this product are not biodegradable. May cause long-term adverse effects in environment.

Bioaccumulative potential

Not established.

Mobility in soil

No additional information available.

Other adverse effects

Avoid release to the environment.

SECTION 13: Disposal considerations

Disposal methods

Product disposal

Dispose of contents/container in accordance with local, regional, national, and international regulations. Do not pierce or burn, even after use.

Sewage disposal

Avoid release into the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

Other disposal recommendations

Container may remain hazardous when empty. Continue to observe all precautions. Do not puncture or incinerate container. Product should be fully characterized prior to disposal.

SECTION 14: Transport information

DOT (US)

UN Number: UN1993

Class: 3

Packing Group: II

Proper Shipping Name: Flammable liquids, n.o.s.

Safety Data Sheet

IMDG

UN Number: UN1993

Class: 3

Packing Group: II

EMS Number: N/A

Proper Shipping Name: Flammable liquids, n.o.s.

IATA

UN Number: UN1993

Class: 3

Packing Group: II

Proper Shipping Name: Flammable liquids, n.o.s.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Massachusetts Right To Know Components (105 CMR 670)

Chemical name: DICHLOROETHYLENE TRANS

CAS number: 156-60-5

Chemical name: DENATURED ALCOHOL

CAS number: 64-17-5

Chemical name: ACETONE

CAS number: 67-64-1

Massachusetts Toxic Use Reduction Act (TURA) list

Chemical name: 1,2-Dichloroethylene (trans)

CAS number: 156-60-5

Chemical name: Acetone

CAS number: 67-64-1

New Jersey Right To Know Components

Common name: ETHYL ALCOHOL

CAS number: 64-17-5

Common name: ACETONE

CAS number: 67-64-1

Pennsylvania Right To Know Components

Chemical name: ETHENE, 1,2-DICHLORO-, (E)-

CAS number: 156-60-5

Chemical name: ETHANOL

CAS number: 64-17-5

Chemical name: 2-PROPANONE

CAS number: 67-64-1

Safety Data Sheet

US EPA TSCA public inventory

Chemical name: Trans-1,2-dichloroethylene

CAS number: 156-60-5

Chemical name: Ethanol

CAS number: 64-17-5

Chemical name: Acetone

CAS number: 67-64-1

SECTION 16: Other information

N/A = Not applicable; N/D = Not determined

16.1 Further information/disclaimer

To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.

16.2 Preparation information

Prepared by: Jessica Wilson

Date prepared: 3-11-2025

