

MEAN GREEN is specially formulated to bond bubble wrap and fiberglass insulation to sheet metal. It is a versatile adhesive that can also bond paper, cloth, wood, metal, foam, rubber, plastic, insulation and many other industrial items. Dries to a slightly tacky, permanently flexible film having excellent physical properties and exceptional resistance to aging. Industrial applications include boxing, taping, knife edging, lamination of foamed products, insulation, aluminum building boards, furniture and automotive upholstery, etc.

DIRECTIONS: Apply: Apply a thin, even coat of Mean Green to both surfaces you wish to bond. **Allow to Tack:** Wait 1-4 minutes (the **Open Time** or **Window of Workability**). The glue should feel slightly tacky to the touch. Do not press surfaces together yet. **Bond:** Once tacky, align the coated surfaces and press them together firmly. **Cure:** Do not disturb the bond for 5-6 minutes. This is the Bonding Time (or **Dry Time**) and may vary depending on the ambient temperature and humidity.

PRECAUTIONARY STATEMENTS: Read **Safety Data Sheet** before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Store locked up. Protect from sunlight. Store in a well-ventilated place. Dispose of contents/container to the specifications of local, regional, and international regulations.



WARNING: This product can expose you to chemicals including perchloroethylene, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

INSTRUCCIONES: Mantenga el cilindro alejado del piso de concreto durante temperaturas bajo cero. Para mejores resultados, use a temperaturas entre 60°F y 90°F. Asegúrese de que todas las superficies a rociar estén limpias y libres de residuos, polvo, suciedad, grasa, etc. Pruebe con la pistola en una superficie de prueba para asegurarse de que el adhesivo fluya. Sostenga la pistola rociadora de 8 a 10 pulgadas de la superficie a rociar. Evite la acumulación de adhesivo o burbujas. Los bordes del patrón de rociado deben superponerse para brindar una cobertura uniforme sobre la superficie.

DECLARACIONES DE PRECAUCIÓN: Obtenga instrucciones especiales antes de su uso. No lo manipule hasta que se hayan leído y comprendido todas las precauciones de seguridad. Evite respirar el polvo/el humo/el gas/la niebla/los vapores/el aerosol. Úselo únicamente al aire libre o en un área bien ventilada. Utilice guantes/ropa protectora/protección para los ojos/protección facial. EN CASO DE INGESTIÓN: Llame inmediatamente a un CENTRO DE ENVENENAMIENTO/médico. EN CASO DE INHALACIÓN: Lleve a la persona al aire libre y manténgala cómoda para respirar. Si ha estado expuesto o preocupado: Obtenga asesoramiento o atención médica. Llame a un CENTRO DE TOXICOLOGÍA/médico si no se siente bien. NO induzca el vómito. Tienda cerrada. Proteger de la luz solar. Almacenar en un lugar bien ventilado. Deseche el contenido/contenedor según las especificaciones de las regulaciones locales, regionales e internacionales.



ADVERTENCIA: Este producto puede exponerlo a productos químicos, incluido el perchloroethylene, que el estado de California reconoce como causante de cáncer. Para obtener más información, visite www.p65warnings.ca.gov.

CONTAINS (CAS#): Perchloroethylene (127-18-4), Trans-1,2-dichloroethylene(156-60-5), Petroleum gases, liquified, sweetened, if they contain >0.1% w/w Butadiene (68476-86-8), Carbon Dioxide (124-38-9), Proprietary Fluorinated Compound -*The exact chemical identity and/or percentage of the composition has been withheld as a trade secret.*

Non-refillable, disposable cylinder - DOT 39 NRC 260/325 M1005. Federal law prohibits transportation if refilled - penalty up to \$500,000 and 5 years imprisonment (49 U.S.C. 5124).

Label#600001501



***CAUTION: Non-Flammable Adhesive Mixture. Contains a component that is flammable in its pure state according to GHS definitions, however when combined in the overall adhesive mixture the adhesive is not flammable in either its liquid or dry states.**