



## VAPCO PRODUCTS, INC.

### Safety Data Sheet Xpress Inject Kitchen Sink

---

#### SECTION 1: Identification

##### 1.1 GHS Product identifier

Product name	Xpress Inject Kitchen Sink
Product number	XPS-5T-KS, XPS-15T-KS, XPS-30T-KS, XPS-60T-KS
Brand	Vapco

##### 1.3 Recommended use of the chemical and restrictions on use

Seal, Protect and increase cooling in A/C systems

##### 1.4 Supplier's details

Name	Vapco Products, Inc.
Address	401 Marshall Road Valley Park, MO 63088 United States
Telephone	(636) 923-2121
Fax	(636) 923-3002
email	info@VapcoProducts.com

##### 1.5 Emergency phone number

(800) 255-3924

---

#### SECTION 2: Hazard identification

##### 2.1 Classification of the substance or mixture

###### GHS classification in accordance with: OSHA (29 CFR 1910.1200, 2024)

- Aspiration hazard, Cat. 1
- Eye damage/irritation, Cat. 2A
- Flammable liquids, Cat. 2
- Toxic to reproduction, Cat. 2
- Skin corrosion/irritation, Cat. 2
- Specific target organ toxicity (repeated exposure), Cat. 2
- Specific target organ toxicity (single exposure), Cat. 3

# Safety Data Sheet

## 2.2 GHS label elements, including precautionary statements

### Pictograms



### Signal word

**Danger**

### Hazard statement(s)

H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

### Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
P302+P352	IF ON SKIN: Wash with plenty of water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see First Aid on this label).
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use dry chemical to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to the specifications of local, regional, national, and international regulations.

## Safety Data Sheet

### 2.3 Other hazards which do not result in classification

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

---

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

##### 1. Distillates (petroleum), hydrotreated heavy paraffinic

Concentration	30 - 70 % (weight)
EC no.	265-157-1
CAS no.	64742-54-7
Index no.	649-467-00-8

##### 2. Silane, ethenyltriethoxy-

Concentration	5 - 40 % (weight)
CAS no.	78-08-0

##### 3. Ethanol

Concentration	2 - 10 % (weight)
EC no.	200-578-6
CAS no.	64-17-5
Index no.	603-002-00-5

##### 4. Toluene

Concentration	0.02 - 0.5 % (weight)
EC no.	203-625-9
CAS no.	108-88-3
Index no.	601-021-00-3

---

## SECTION 4: First-aid measures

### 4.1 Description of necessary first-aid measures

General advice	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
If inhaled	First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing. Get medical advice/attention.
In case of skin contact	Immediately drench affected area with water for at least 15 minutes. Remove contaminated clothing immediately. Obtain medical attention if irritation develops or persists.
In case of eye contact	Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.
If swallowed	Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

## Safety Data Sheet

### 4.2 Most important symptoms/effects, acute and delayed

**Symptoms/Injuries:** Causes serious eye irritation.

**Symptoms/Injuries After Inhalation:** May cause respiratory irritation.

**Symptoms/Injuries After Skin Contact:** May cause skin irritation.

**Symptoms/Injuries After Eye Contact:** Causes serious eye irritation. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

**Symptoms/Injuries After Ingestion:** May be fatal if swallowed and enters airways.

**Chronic Symptoms:** None expected under normal conditions of use.

### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

---

## SECTION 5: Fire-fighting measures

### 5.1 Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, dry chemical, or sand. Use appropriate media for surrounding fire.

### 5.2 Specific hazards arising from the chemical

**Explosion Hazard:** Container may explode in heat of fire. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. May form flammable/explosive vapor-air mixture. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. May have flammable/explosive vapor-air mixture.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3 Special protective actions for fire-fighters

**Precautionary Fire Measures:** Exercise caution when fighting any chemical fire.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection. Wear NIOSH-approved Self-Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires.

**Firefighting Instructions:** Use dry chemical, foam, or carbon dioxide (CO<sub>2</sub>). Do not breathe fumes from fire or vapors from decomposition. Do NOT fight fire when fire reaches containers. Evacuate area. Fight fire remotely due to the risk of explosion. Shut off all sources of ignition. Use water spray or fog for cooling exposed containers.

**Hazardous Combustion Products:** Carbon oxide(s). May release flammable gases.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe vapors, spray, mist, gas. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

#### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so.

#### For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedure:** Eliminate ignition sources first, then ventilate the area. Evacuate unnecessary personnel, isolate, and ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### 6.2 Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

## Safety Data Sheet

### 5.3 Methods and materials for containment and cleaning up

**For Containment:** Ventilate the area. Contain any spills with dikes or absorbents to prevent further migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Eliminate all ignition sources. Ventilate area. Stop the ignition source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Take up liquid spill into absorbent material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

**Waste Disposal:** Dispose of in accordance with local, regional, national, and international regulations. Containers may be hazardous when empty. Do not flame cut, braze, or weld. Product should be fully characterized prior to disposal (40 CFR 261).

#### Reference to other sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

**Precautions for Safe Handling:** Do not handle until all safety precautions have been read and understood. Avoid contact with skin, eyes and clothing. Do not breathe gas, mist, spray, vapors. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not spray on open flame or other ignition source.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

**Other Precautions:** Keep out of reach of children. Follow label instructions. Vapors may collect in low lying areas.

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

### 7.2 Conditions for safe storage, including any incompatibilities

**Technical Measures:** Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

**Storage Conditions:** Store in a dry, cool place. Keep only in the original container in a cool, well-ventilated place away from ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

**Incompatible Materials:** Heat sources, strong acids, strong bases, strong oxidizer.

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### 1. Ethanol (CAS: 64-17-5)

TWA [Ethyl alcohol] (Inhalation): 1000 ppm; 1880 mg/m<sup>3</sup>; AU (AU/SWA)

PEL [Ethyl alcohol (Ethanol)] (Inhalation): 1000 ppm; US (US/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL [Ethyl alcohol (Ethanol)] (Inhalation): 1900 mg/m<sup>3</sup>; US (US/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

PEL [Ethyl alcohol (Ethanol)] (Inhalation): 1000 ppm; US (Cal/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

REL [Ethyl alcohol (Ethanol)] (Inhalation): 1000 ppm; US (NIOSH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 2. Toluene (CAS: 108-88-3)

TWA (Inhalation): 50 ppm; 191 mg/m<sup>3</sup>; AU (AU/SWA)

Other advisory: Sk

## Safety Data Sheet

STEL (Inhalation): 150 ppm; 574 mg/m<sup>3</sup>; AU (AU/SWA)

Other advisory: Sk

IOELV-LTEL (Inhalation): 192 mg/m<sup>3</sup>; EU (EU/OSHA)

Skin designation: Yes. List no. 2 under Council Directive 98/24/EC as amended. List last updated on 8/25/2023.

IOELV-LTEL (Inhalation): 50 ppm; EU (EU/OSHA)

Skin designation: Yes. List no. 2 under Council Directive 98/24/EC as amended. List last updated on 8/25/2023.

IOELV-STEL (Inhalation): 384 mg/m<sup>3</sup>; EU (EU/OSHA)

Skin designation: Yes. List no. 2 under Council Directive 98/24/EC as amended. List last updated on 8/25/2023.

IOELV-STEL (Inhalation): 100 ppm; EU (EU/OSHA)

Skin designation: Yes. List no. 2 under Council Directive 98/24/EC as amended. List last updated on 8/25/2023.

### 8.2 Appropriate engineering controls

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Use only outdoors or in well-ventilated area. Ensure all local, regional, national, and international regulations are being observed. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

### 8.3 Individual protection measures, such as personal protective equipment (PPE)

#### Eye/face protection

Chemical safety goggles. Insufficient ventilation: wear respiratory protection. Respiratory protection of the dependent type.

#### Skin protection

Wear protective gloves and clothing.

#### Body protection

Wear suitable protective clothing. Wear protective gloves. Chemical resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

#### Respiratory protection

Use a NIOSH-approved Self-Containing Breathing Apparatus whenever exposure may exceed established Occupational Exposure Limits.

---

## SECTION 9: Physical and chemical properties

### Basic physical and chemical properties

Physical state	Liquid
Appearance	Liquid
Color	Yellow/green/brown
Odor	Hydrocarbon odor
Odor threshold	N/A
Melting point/freezing point	-114°C (-173°F)
Boiling point or initial boiling point and boiling range	78°C (173°F)
Flammability	N/A
Lower and upper explosion limit/flammability limit	N/D
Flash point	13°C (55°F)
Auto-ignition temperature	363°C (685°F)
Decomposition temperature	N/A
pH	N/A

## Safety Data Sheet

Kinematic viscosity	N/A
Solubility	N/A
Partition coefficient n-octanol/water (log value)	N/D
Vapor pressure	N/D
Evaporation rate	N/A
Density and/or relative density	0.7893 g/cm <sup>3</sup> at 20°C
Relative vapor density	N/A

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc. Highly flammable liquid and vapor.

#### 10.2 Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4 Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks. Incompatible materials.

#### 10.5 Incompatible materials

Heat sources, strong acids, strong bases, strong oxidizing agents.

#### 10.6 Hazardous decomposition products

Carbon oxide(s).

---

### SECTION 11: Toxicological information

#### Information on toxicological effects

##### Acute toxicity

Ethyl alcohol: (64-17-5)

LD50 Oral - Rat - 7,060 mg/kg

LC50 Inhalation - Rat - 20,000 ppm - 10 hrs

LC50 Dermal - Rat - 20 mg/kg

Toluene: (108-88-3)

LD50 Oral - Rat - >5,580 mg/kg

LC50 Inhalation - Rat - 12,500-28,800 mg/m<sup>3</sup> - 4 hrs

LD50 Dermal - Rabbit - 12,196 mg/kg

Silane, ethenyltriethoxy-: (78-08-0)

LD50 Dermal - Rabbit - 9,100 mg/kg

##### Skin corrosion/irritation

Serious eye damage/eye irritation.

##### Serious eye damage/irritation

Causes serious eye irritation.

## Safety Data Sheet

### Respiratory or skin sensitization

Not classified.

### Germ cell mutagenicity

Not classified.

### Carcinogenicity

Not classified.

### Reproductive toxicity

Damage to fetus possible. Suspected human reproductive toxicant.

---

### Specific target organ toxicity (STOT) - single exposure

Inhalation - May cause respiratory irritation.

### Specific target organ toxicity (STOT) - repeated exposure

Not classified.

### Aspiration hazard

Not classified.

### Additional information

**Symptoms/Injuries:** Causes serious eye irritation.

**Symptoms/Injuries After Inhalation:** May cause respiratory irritation.

**Symptoms/Injuries After Skin Contact:** May cause skin irritation.

**Symptoms/Injuries After Eye Contact:** Causes serious eye irritation. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

**Symptoms/Injuries After Ingestion:** May be fatal if swallowed and enters airways.

**Chronic Symptoms:** None expected under normal conditions of use.

---

## SECTION 12: Ecological information

### Toxicity

Toluene: (108-88-3)

LC50 - *Oncorhynchus mykiss* (rainbow trout) - 7.63 mg/l - 96 hrs

NOEC - *Pimephales promelas* (fathead minnow) - 5.44 mg/l - 7 days

EC50 - *Daphnia magna* (water flea) - 8.00 mg/l - 24 hrs

EC50 - *Daphnia magna* (water flea) - 6 mg/l - 48 hrs

EC50 - *Chlorella vulgaris* (fresh water algae) - 245.00 mg/l - 24 hrs

EC50 - *Pseudokirchneriella subcapitata* (green algae) - 10.00 mg/l - 24 hrs

### Persistence and degradability

No data available.

### Bioaccumulative potential

No data available.

### Mobility in soil

No data available.

### Other adverse effects

Avoid release to the environment.

# Safety Data Sheet

---

## SECTION 13: Disposal considerations

### Disposal methods

#### Product disposal

Contact a licensed professional waste disposal service to dispose of this material. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

#### Packaging disposal

Dispose of as unused product.

#### Other disposal recommendations

Container may remain hazardous when empty. Continue to observe all precautions. Do not puncture or incinerate container. Product should be fully characterized prior to disposal. Dispose of contents/container in accordance with local, regional, national, and international regulations. Do not pierce or burn, even after use.

---

## SECTION 14: Transport information

### DOT (US)

UN Number: UN1268

Class: 3

Packing Group: II

Proper Shipping Name: Petroleum distillates, n.o.s. or Petroleum products, n.o.s.

### IMDG

UN Number: UN1268

Class: 3

Packing Group: II

EMS Number: N/A

Proper Shipping Name: Petroleum distillates, n.o.s. or Petroleum products, n.o.s.

### IATA

UN Number: UN1268

Class: 3

Packing Group: II

Proper Shipping Name: Petroleum distillates, n.o.s. or Petroleum products, n.o.s.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### California Prop. 65 components

Chemical name: Toluene

CAS number: 108-88-3

01/01/1991 - Developmental toxicity

08/07/2009 - Female reproductive toxicity

#### California Proposition 65 Chemicals List

WARNING: This product contains chemicals known to the State of California to cause cancer. WARNING: This product contains chemicals known to the State of California to cause birth defects.

WARNING: This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## Safety Data Sheet

### Massachusetts Right To Know Components (105 CMR 670)

Chemical name: DENATURED ALCOHOL

CAS number: 64-17-5

Chemical name: METHYLBENZENE

CAS number: 108-88-3

### Massachusetts Toxic Use Reduction Act (TURA) list

Chemical name: Toluene

CAS number: 108-88-3

### New Jersey Right To Know Components

Common name: ETHYL ALCOHOL

CAS number: 64-17-5

Common name: TOLUENE

CAS number: 108-88-3

### Pennsylvania Right To Know Components

Chemical name: ETHANOL

CAS number: 64-17-5

Chemical name: BENZENE, METHYL-

CAS number: 108-88-3

### SARA 311/312 Hazards

Immediate (Acute) Health Hazard, Fire Hazard

### US EPA TSCA public inventory

Chemical name: Ethanol

CAS number: 64-17-5

Chemical name: Toluene

CAS number: 108-88-3

Chemical name: Silane, ethenyltriethoxy-

CAS number: 78-08-0

Chemical name: Distillates (petroleum), hydrotreated heavy paraffinic

CAS number: 64742-54-7

---

## SECTION 16: Other information

N/A = Not applicable; N/D = Not determined

### 16.1 Further information/disclaimer

To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which

## Safety Data Sheet

exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.

### 16.2 Preparation information

Prepared by: Jessica Wilson

Date prepared: 1/22/2026



2

3

4

5

6

7

8

9

10